

*"Demanded by Those Who Know Quality"*

## FLOW GATE

### S T A N D A R D F E A T U R E S :

- Universally mounted to the right side of the moldboard, easily removable with the pull of a pin
- More even distribution of material, and the ability to hold a straighter line
- Adjustable up to 90° (45° in or out) 3/8" moldboard, 1/2" adjusting mechanism, and a 5/8" replaceable cutting edge



Designed with quality and durability in mind, the Flow Gate is used to carry a windrow from the end of the moldboard for longer distances than with a conventional motor grader moldboard. The result is a more even distribution of material, while holding a straighter line when working the shoulder of the road or wherever even distribution of material may be required, including aggregate material and hot

asphalt. When used in conjunction with the Bonnell Road Widener, the Flow Gate makes secondary road widening projects a breeze, and because removal is done with just the pull of a pin, your motor grader is ready to go back to work on other project's without lengthy conversion times.

# Flow Gate Specifications

Moldboard Construction:	3/8"
Adjusting Plate & Mounting Bracket:	1/2"
Adjustment(s):	Manual via (2) 5/8" pins, Up to 90° (45° in or out)
Pivot Pin / Disconnect Pin:	1 1/4" Diameter
Cutting Edge:	5/8" x 6", Punched to AASHTO Standard
Finish:	Black



Sold By:



1385 Franklin Grove Rd. • Dixon, IL 61021 • [www.bonnell.com](http://www.bonnell.com)  
(815) 284-3819 • (800) 851-9664 • Fax (815) 284-8815

Bonnell Industries reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.  
© 2006 Bonnell Industries, Inc. | 0306

