

*"Demanded by Those Who Know Quality"*

## WINDROW ELIMINATOR

### STANDARD FEATURES:

- Crank adjustable moldboard swing and gauge wheels
- Quick attach and detach
- 5/8" x 8" Hi Carbon steel cutting edge, standard Hiway punching
- Swivel and float features
- One double acting lift cylinder included
- Custom mounting brackets



Compliment your motor grader with the Windrow Eliminator. One pass fuel efficiency, combined with low maintenance and legendary Bonnell quality makes it the professional's choice in road maintenance equipment.

The Windrow Eliminator will strike off the windrow left behind the motor grader eliminating the need for a second pass. The finish grade is set by the parallel lift hitch and the pneumatic wheels. Specify a Bonnell Windrow Eliminator and you will never chase another windrow.

# Windrow Eliminator Specifications

Specifications	Model	110	111	112	113	114	115
Moldboard Width		10 ft	11ft	12 ft	13 ft	14 ft	15 ft
Cutting Edge Width							
with Extensions		11 ft	12 ft	13 ft	14 ft	15 ft	16 ft
Cutting Edge Construction		5/8" x 8" Hi Carbon Steel with Standard Hi-way Punch					
Moldboard Height with							
Cutting Edge		11"	13"	13"	13"	13"	13"
Moldboard Construction		Reinforced Steel Angle - adjustable 6" right or left of center					
Moldboard Swing		Manual Crank - No Tools Required					
Running Gear		8" 4 ply High Speed					
Pneu. Wheel & Tire		Pneumatic Wheel & Tire					
Hydraulics		One Double Acting Lift Cylinder					
Finish		Bonnell Orange					
Shipping Weight		1100 lbs	1850 lbs	1864 lbs	1878 lbs	1892 lbs	1906 lbs

## General

The Windrow Eliminator is a single blade, adjustable manual swing and oscillation. This unit is designed to strike off and level out the windrow of material created by a typical motor grader, making a two-pass operation into a one-pass operation.

## Lifting Frame

The lift frame is a heavy-duty constructed, professionally manufactured

Sold By:



1385 Franklin Grove Rd. • Dixon, IL 61021 • [www.bonnell.com](http://www.bonnell.com)  
 (815) 284-3819 • (800) 851-9664 • Fax (815) 284-8815

Bonnell Industries reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.  
 © 2006 Bonnell Industries, Inc. | 0306

# Options

Moldboard  
 Standard models 110 (10')  
 up to 115 (15')

Tires  
 5.70" x 8" pneumatic caster wheels,  
 adjustable in height without tools.

Paint  
 Sand blasted and painted  
 Bonnell orange.

Options  
 • Hydraulic Swing  
 • Hydraulic Wheel Adjustment

